

We claim:

1. A telecommunication system that allows communication between a circuit-based wireless telephony network and a packet-based Internet telephony network, the system comprising:

5 a circuit-based wireless telephony network providing wireless access to the system;

a packet-based Internet telephony network providing Internet telephony access to the system; and

10 a base station gateway controller for providing an interface between the wireless telephony network and the Internet telephony network.

2. The system of claim 1, wherein the system does not require utilization of the Public Switched Telephone Network.

15 3. The system of claim 1, wherein the base station gateway controller is controlled by a call processing engine.

4. The system of claim 1, wherein the base station gateway controller provides a data signal transport gateway between circuit-based data and packet-based data.

20 5. The system of claim 4, wherein the circuit-based data and the packet based data are voice data.

6. The system of claim 1, wherein the base station gateway controller is configured to perform vocoding functions to translate between different data coding schemes.

7. The system of claim 1, comprising a packet-based mobile switching center  
5 communicatively connected with the base station gateway controller.

8. The system of claim 1, comprising:  
a packet-based mobile switching center communicatively connected with the base  
station gateway controller; and

10 one or more circuit-based base station controllers communicatively connected to  
the base station gateway controller, wherein the base station gateway controller is utilized  
as a media gateway for communications between the mobile switching center and the one  
or more base station controllers.

15 9. The system of claim 8, wherein the base station gateway controller provides a  
data signal transport gateway between circuit-based data and packet-based data.

10. The system of claim 9, wherein the communications are voice data  
communications.

20 11. The system of claim 8, wherein the base station gateway controller is configured  
to perform vocoding functions to translate between different data coding schemes.

0903518-03201

12. The system of claim 1, wherein the circuit-based wireless telephony network is a Global System for Mobile Communications network.

13. The system of claim 1, wherein the circuit-based wireless telephony network is a  
5 Universal Mobile Telecommunications System network.

14. The system of claim 1, wherein the Internet telephony network is an Internet Protocol network.

10 15. The system of claim 14, wherein the Internet Protocol network is a Session Initiation Protocol network.

16. The system of claim 14, wherein the Internet Protocol network is a H.323  
15 network.

17. A method for facilitating communication between a first device, the first device being a packet-based Internet telephony network based device, and a second device, the second device being a circuit-based wireless telephony network based device, by facilitating connection of a call from the first device to the second device, the method  
20 comprising:

registering, at a serving Mobile Switching Center, a Mobile Station ISDN associated with the second device;

utilizing an Enum database to map the Mobile Station ISDN to a Session Initiation Protocol address associated with a home Session Initiation Protocol Registrar associated with the second device;

obtaining, at the Mobile Switching Center, the Session Initiation Protocol address;

5 and

utilizing the Session Initiation Protocol address in connecting the call.

18. The method of claim 17, wherein the method comprises utilizing a modified registration procedure.

10

19. The method of claim 17, wherein the method comprises utilizing a modified mobile switching station.

15

20. The method of claim 17, wherein the second device is based on a Global System for Mobile Communications network.

21. The system of claim 17, wherein the second device is based on a Universal Mobile Telecommunications System network.

20

22. A method for facilitating communication between a first device, the first device being a packet-based Internet telephony network based device, and a second device, the second device being a circuit-based wireless telephony network based device, by

0503548-00001

facilitating connection of a call from the first device to the second device, the method comprising:

receiving, at a home Session Initiation Protocol proxy server associated with the first device, an invite to connect the call;

5 the home Session Initiation Protocol proxy server determining a Mobile Station ISDN associated with the second device;

utilizing a Home Location Register to map the mobile station ISDN to a Mobile Station Routing Number associated with the second device;

10 utilizing an Enum database to map the Mobile Station Routing Number to a Session Initiation Protocol address associated with a serving mobile switching center associated with the second device; and

utilizing the Session Initiation Protocol address in connecting the call.

15 23. The method of claim 22, wherein the method comprises a modified registration procedure.

24. The method of claim 22, wherein the method comprises utilizing a modified Session Initiation Protocol proxy server.

20 25. The method of claim 22, wherein the second device is based on a Global System for Mobile Communications network.

05933618-03201  
FOIA b 7 - D

26. The method of claim 22, wherein the second device is based on a Universal Mobile Telecommunications System network.

27. A method for facilitating communication between a first device, the first device being a packet-based Internet telephony network based device, and a second device, the second device being a circuit-based wireless telephony network based device, by facilitating connection of a call from the first device to the second device, the method comprising:

receiving, at a Home Location Register, a first network address associated with a serving Mobile Switching Center associated with the second device; utilizing an Enum database to map the first network address to a Session Initiation Protocol domain name; receiving, at a Home Location Register, the Session Initiation Protocol domain name; receiving, at a Session Initiation Protocol proxy server, an invite to connect the call; the Session Initiation Protocol proxy server querying the Home Location Register to obtain the Session Initiation Protocol domain name; and utilizing the Session Initiation Protocol domain name in connecting the call.

28. The method of claim 27, wherein the method comprises a modified registration procedure and a modified call set up procedure.

29. The method of claim 27, wherein the method comprises utilizing a modified Home Location Register.

30. The method of claim 27, wherein the second device is based on a Global System  
5 for Mobile Communications network.

31. The method of claim 27, wherein the second device is based on a Universal Mobile Telecommunications System network.

10 32. The method of claim 27, wherein the first network address is an E.164 address.

33. A method for facilitating communication between a first device, the first device  
being a packet-based Internet telephony network based device, and a second device, the  
second device being a circuit-based wireless telephony network based device, by  
15 facilitating connection of a call from the first device to the second device, the method  
comprising:

a registration procedure, comprising:

receiving, at a Home Location Register, a first network address associated  
with a serving Mobile Switching Center associated with the second device;

20 utilizing an Enum database to map the first network address to a Session  
Initiation Protocol domain name; and

receiving, at a Home Location Register, the Session Initiation Protocol  
domain name; and

a call set up procedure, comprising:

receiving, at a Session Initiation Protocol proxy server, an invite to  
connect the call;

the Session Initiation Protocol proxy server querying the Home Location

5 Register to obtain the Session Initiation Protocol domain name; and

utilizing the Session Initiation Protocol domain name in connecting the  
call.

09318-08201  
FO2280-8T5560